




Short spigot injection moulded Reduction



Description

Long spigot stub end for applications under pressure, manufactured by injection moulding of high-density polyethylene in accordance with standards EN12201-3 and EN1555-3.

The fitting is supplied by a company operating under a quality system according to UNI EN ISO 9001:2015, certified and validated by an accredited third party.

Dimensions

DN/OD	DN1/OD1	H	H1	Z	SDR
mm	mm	mm	mm	mm	-
250	160	58	55	163	26÷7,4
250	180	62	50	155	26÷7,4
250	200	58	50	140	26÷7,4
250	225	50	68	150	26÷7,4
280	200	71	50	161	26÷7,4
280	225	71	55	154	26÷7,4
280	250	71	63	148	26÷7,4
315	225	80	55	184	26÷7,4
315	250	80	63	179	26÷7,4
315	280	80	75	174	26÷7,4
355	225	90	55	213	26÷11
355	250	86	63	196	26÷7,4
355	280	86	75	200	26÷7,4
355	315	86	84	187	26÷7,4
400	280	95	75	227	26÷7,4
400	315	95	84	222	26÷7,4
400	355	95	93	209	26÷7,4
450	315	62	84	224	26÷7,4
450	355	62	93	204	26÷7,4
450	400	62	98	190	26÷7,4
500	355	60	93	230	26÷11

Correspondence SDR - PN - Series


SDR	PN (PE100)	S (EN 1555)
26	6	-
17	10	8
11	16	5
7,4	25	-

The Company reserves the right to change the dimensional characteristics listed in the table without prior notice while maintaining the performance indicated.





Short spigot injection moulded Reduction



DN/OD	DN1/OD1	H	H1	Z	SDR
500	400	60	98	210	26÷11
500	450	60	65	165	26÷7,4
560	400	53	98	240	26÷7,4
560	450	57	65	185	26÷7,4
560	500	57	67	163	26÷11
630	450	58	65	230	26÷11
630	500	63	62	206	26÷11
630	560	63	63	186	26÷11
710	560	65	40	160	26÷11
710	630	65	62	160	26÷11
800	710	62	60	160	26÷11
900	800	62	62	165	26÷11
1000	900	65	56	170	26÷11
1200	1000	58	45	165	26÷17

