




Short spigot stub end for water/gas under pressure



Description

Short spigot stub end for applications under pressure, manufactured by injection moulding of high-density polyethylene in accordance with standards EN12201-3 and EN1555-3.

The fitting is supplied by a company operating under a quality system according to UNI EN ISO 9001:2015, certified and validated by an accredited third party.

SDR26


Dimensions

DE	H	F	B	C	A
mm	mm	mm	mm	mm	mm
160	25	31	175	206	14
180	76	6	183	206	16
200	50	46	232	261	19
225	35	40	235	261	19
250	41	39	285	316	20
280	72	19	291	316	20
315	74	35	335	372	20
355	60	37	373	422	24
400	58	31	427	472	26
450	63	41	514	577	36
500	60	25	530	577	37
560	54	38	615	678	40
630	44	36	642	678	40
710	35	41	737	782	52
800	30	47	840	888	43
900	40	43	944	988	47
1000	40	38	1047	1088	52
1200	35	55	1245	1305	63





Short spigot stub end for water/gas under pressure



SDR17


Dimensions

DE	H	F	B	C	A
mm	mm	mm	mm	mm	mm
63	27	23	75	103	14
75	27	24	89	123	16
90	26	26	105	139	17
110	25	30	125	159	18
125	30	28	132	159	18
140	30	32	155	189	18
160	25	32	175	213	18
180	76	6	180	213	20
200	41	50	232	269	24
225	35	40	235	269	24
250	45	39	285	321	25
280	66	20	291	321	25
315	65	42	335	371	25
355	51	43	373	431	30
400	52	36	427	483	33
450	67	31	514	586	45
500	60	24	530	594	45
560	54	31	615	686	50
630	46	35	642	694	50
710	35	41	737	801	52
800	40	32	840	906	53
900	40	31	944	1006	59
1000	40	30	1047	1111	65
1200	35	56	1245	1331	79





Short spigot stub end for water/gas under pressure



SDR11


Dimensions

DE	H	F	B	C	A
mm	mm	mm	mm	mm	mm
63	23	23	75	103	14
90	26	27	105	139	17
110	32	25	125	159	18
125	26	24	132	159	24
140	30	31	155	189	25
160	40	31	175	213	25
180	65	2	183	213	30
200	50	47	232	269	32
225	28	44	235	269	32
250	39	42	285	321	35
280	68	25	291	321	35
315	81	36	335	371	35
355	51	44	373	431	40
400	56	36	427	483	45
450	65	32	514	594	60
500	30	40	530	607	60
560	50	36	615	702	60
630	55	23	642	710	65
710	35	40	737	801	75
800	30	40	840	906	80
900	28	40	944	1006	90





Short spigot stub end for water/gas under pressure



SDR7.4

Dimensions

DE	H	F	B	C	A
mm	mm	mm	mm	mm	mm
315	82	36	335	392	47
355	52	43	373	449	53
400	58	33	427	506	60
450	67	26	514	616	67
500	60	21	530	616	74
560	54	38	615	723	83

Correspondence SDR - PN – Series

SDR	PN (PE100)	S (EN 1555)
26	6	-
17	10	8
11	16	5
7,4	25	-

The Company reserves the right to change the dimensional characteristics listed in the table without prior notice while maintaining the performance indicated.

